



LED MODULE D1000/LM160




LED type	SMD2835
dimensions	160 x 18mm
power	3W
color temperature	5700 - 6000K
beam angle	160°
emitted light	135lm/W
IP class	24
light decay	<5%/Year
operating current	220 - 240mA

LED MODULE D1000/LM220




LED type	SMD2835
dimensions	220 x 18mm
power	4W
color temperature	5700 - 6000K
beam angle	160°
emitted light	135lm/W
IP class	24
light decay	<5%/Year
operating current	220 - 240mA

LED MODULE D1000/LM310




LED type	SMD2835
dimensions	310 x 18mm
power	5W
color temperature	5700 - 6000K
beam angle	160°
emitted light	135lm/W
IP class	24
light decay	<5%/Year
operating current	220 - 240mA

LED MODULE D1000/LM400



LED type	SMD2835
dimensions	400 x 18mm
power	6W
color temperature	5700 - 6000K
beam angle	160°
emitted light	135lm/W
IP class	24
light decay	<5%/Year
operating current	220 - 240mA

LED MODULE D1000/LM520




LED type	SMD2835
dimensions	520 x 18mm
power	10W
color temperature	5700 - 6000K
beam angle	160°
emitted light	135lm/W
IP class	24
light decay	<5%/Year
operating current	220 - 240mA

DRIVER D1000/10-25W



ДРАЙВЕР D1000/1025x2 (with two output cables)




dimensions **40/27/22mm**
power **10-25W**
input **AC 165-265V 50/60Hz**
output **DC 30-90V 240mA**
IP class **24**

DRIVER D1000/30-60W



ДРАЙВЕР D1000/3060x2 (with two output cables)



dimensions **67/30/22mm**
power **30-60W**
input **AC 165-265V 50/60Hz**
output **DC 110-180V 240mA**
IP class **24**

CONNECTING CABLE 80mm D1000/C080



length **80mm**

CONNECTING CABLE 150mm D1000/C150



length **150mm**

CONNECTING CABLE 250mm D1000/C250



length **250mm**

END CAP D1000/2 PINS



2 Pin